

S4/1PCT-W2 (P.169-TW)**Product summary:**

DiSEqC 1.0&1.1&1.2 switch, terr. by-pass

Brief description:

4in/1out universal DiSEqC switch designed for use in various reception strategies and for 1 subscriber. One of the satellite inputs transmits terrestrial signals.

Although it can be used as standard DiSEqC 1.0 switch, it's unique features predetermine it for use as "Uncommitted" DiSEqC 1.1 switch or as DiSEqC 1.2 to DiSEqC 1.0 transcoder, allowing to extent multiswitch system for up to 16 quatro/quad LNBs. Please read carefully Instruction Manual before purchase and setting up.

**Technical data:**

Parameter	Condition	Value
Frequency range	Sat. inputs	950-2300 MHz
	LNB+Terr. input 2	5-862, 950-2300 MHz,
	Output	5-2300 MHz,
Control		DiSEqC 1.0, 1.1, 1.2 commands
Insertion loss	Sat.	5 dB avg
	Terr.	5 dB avg
Sat. inputs isolation		25 dB min
Power consumption	From receiver	35 mA (18V) + LNB
	DC current pass	400 mA max
Dimensions (w,d,h)		11.2 x 11.2 x 4.9 cm
Temperature range		-30 ~ +70°C
Weight		0.260 kg