

Product summary

EoC SAT+TV+data terminal

Brief description

The device is an EoC terminal to convert UTP cable to 75 ohm coaxial cable and vice versa.

The device allows to replace the UTP cable with a coaxial cable up to 200 meters of length.

No settings are required, just connect the device according to the picture below. For the external power, use our original power adapter 9-12V DC.

The NT11 terminal works in connection with any Ethernet devices according to 100BASE-TX and 10BASE-T standard.

When two NT11 terminals are connected together using a coaxial cable, the coaxial cable should not be interrupted by any cable connector or other device. If this can not be avoided and it is necessary to use a cable connector, use only quality connectors for coaxial cables with an impedance of 75 ohm.



Technical data

| Parameter | Condition | Value |
|--------------------|------------|--------------------|
| Data | RJ45 port | 100 Mbit/s |
| | Coax | 100 Mbit/s |
| Power consumption | LAN active | 50 mA / 12V |
| Dimensions (w,d,h) | | 5.4 x 6.0 x 3.2 cm |
| Temperature range | | -25 ~ +60 °C |

Postal address: EMP-Centauri s.r.o. 5. května 690 339 01 Klatovy Czech Republic

Management: Tel.: +420 376 323 813 Tel.: +420 603 497 419 E-mail: info@emp-centauri.cz

Sales department: Tel.: +420 376 323 813 Tel.: +420 603 497 419 Tel.: +420 776 619 976 (EN) Tel.: +420 778 066 654 (CZ) E-mail: sales@emp-centauri.cz

Purchase department: E-mail: purchase@emp-centauri.cz

Technical support: Tel.: +420 376 323 853 (during workhours) Hotline: +420 603 497 419 (available anytime) E-mail:

support@emp-centauri.cz Skype ID : **live::cid.624e3941fb5334d9**